

sewoo

Board on the economic class being served with a great performance.

LK-P25



- Competitive low price
- Ultra Compact and Lightweight
- Micro USB Interface supported
- Excellent Compatibility
- NFC for easy Bluetooth pairing
- Durable design with Drop resistant
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap & Case, Belt Clip & Case



Bluetooth



Barcode



Portable



Durable



Rugged Design



Drop Resistant



Wireless Connectivity



Easy Loading



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support



APPLICATION



SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
Up to 2.3ips (60mm/sec)

Print Width
Up to 1.8" (48mm)

Resolution
203 dpi (8dots/mm)

Battery Voltage / Capacity
3.7V / 2600mAh.
Rechargeable Li-ion battery

Battery Charge Time
Adaptor : Max. 3.3Hrs
USB : Max. 6Hrs

Standby Time
71Hrs

Sensor
Paper end, Cover open,
Black mark

Reliability
TPH life : 50km

PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
3.1" × 1.74" × 4.06"
(79 × 44.4 × 103.2mm)

Weight
0.4lb(189g, Battery Incl.)

INTERFACES

Standard
USB, Bluetooth 4.2 classic
and Low Energy (BLE)

CERTIFICATIONS

KC, CE, FCC, UL/cUL, Mfi, UKCA

OPERATING CHARACTERISTICS

Operating Temperature
14 ~ 122°F(-10 ~ 50°C)

Operating Humidity
10 ~ 80%

Storage Temperature
-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity
10 ~ 90%

Drop Rating
5ft/1.5m (set only) to concrete
6ft/1.8m with case to concrete

BARCODES

1D
UPC-A, UPC-E, EAN-8, Code39, Code93,
ITF, Codabar, EAN-13, Code128

2D
QR, PDF417, Maxicode, Datamatrix

SOFTWARE

Emulations
ESC/POS Compatible

Drivers
Windows Driver(10, 2012, 8, 7, 2008,
VISTA, 2003, XP, 32bit & 64bit),
Window CE & Mobile Driver & SDK
(CE 4.2~, Mobile 5.0~), Linux Driver,
Mac Driver, OPOS Driver, JavaPOS Driver,
iOS SDK, Android(2.1~) SDK

MEDIA CHARACTERISTICS

Media Type
Thermal paper

Media Width
2.2" (58mm)

Media Core Diameter
0.4" (12.5mm)

Media Roll Diameter
1.5" (40mm)

Thickness
0.06mm

FONTS / GRAPHICS

Character Type
Font A(12x24), Font B(9x17),
Chinese(Traditional/Simplified, 24x24),
Korean(24x24), Japanese(24x24)

Characters per Line (CPL)
Font A(12x24): 32cpl,
Font B(9x17): 42cpl,

Character Set
95 Alphanumeric,
14 International,
128 x 18 Graphic

ACCESSORIES

Standard
USB Cable, Battery Pack,
Thermal Roll Paper,
Belt Clip & Battery Cover
AD/DC Adaptor 5VDC

Optional
Leather Case, Shouder Strap



Monterrey | Chihuahua | Ciudad de México | Guadalajara | Mazatlán

Tel. +52 (81) 8881 1080 Ext 1004 Cel. +52 (81) 2747 6654 E-mail. lcardenas@bnext.mx